

HEAT SMOKE DETECTOR

WIRELESS INTERCONNECTABLE PHOTOELECTRIC



TESSMHT415H07

Mains Powered 240Vac HEAT Photoelectric Smoke Alarm with Battery backup.

Box: QUANTITY 40

The unit is a 220-240VAC with 9VDC battery backup heat alarm. Heat alarm can give off warnings when ambient temperature between 54°C-70°C. The abnormal temperature may result from dangerous fire situation. In that case the dangerous situation of dwelling and notice people to evacuate right away. If the alarm is interconnected with other heat alarms, they would give off evacuated warnings at the same time.

SPECIFICATIONS

- Temperature Range 0-40 degrees
- Humidity Range 10%-93%
- Alarm volume > 85dB(A)
- Dimensions: 132mm (d) x 553mm (H)
- Conforms to AS3786:2014

FEATURES

- WIRELESS interconnect up to 48 units, wired 24 units max
- Wireless distance up to 60m within clear line of sight, wired 150m
- Hush function easy to use test button
- 9V DC battery
- Loop terminal provided
- Hinged detachable base – easy push button open
- LED indicators
- 'Low Battery' audible warning
- Discrete slimline appearance
- No need for large ceiling cut away, base recessed for mains cabling
- Interconnectable with SMPHE_514ED via wireless interconnection module, providing a complete hardwired and wireless install
- Compatible with Remote Controller SARC
- Colour – White
- 5 Year Warranty

SCAN
HERE



Please email all orders to
sales@gtsonline.com.au

Electrical Best Pty Ltd ABN: 38 631 960 711, trading as
General Trade Supplies
36 Terrence Road Brendale Qld 4500
Ph: + 61 7 3881 6115 FAX: + 61 7 3881 6120