











PRODUCT DATA AND APPLICATION SHEET

PRODUCT NAME **Tesla Industrial Straight & Angled Plugs**

DESCRIPTION

Tesla IP56 industrial plugs range of straight and angled plugs are all fitted with a screwed ring for securing to socket outlets and to ensure IP66 rating. Design innovations include a transparent centre body section for instant visual checking of connections and an internal clamp which grips two ways to prevent cable twisting.

Model	Angled Model	Description	Rating (AMP)	Voltage (V)	Conductor Terminal Size in mm ²		Cable Nominal Diameter		No of Phase	Configuration
					Min.	Max.	Min.	Max.		
TP410	TPA410	4 Pin 10 A Round Pin Plug	10	500	2.5	4	7	16	3	
TP420	TPA420	4 Pin 20 A Round Pin Plug	20	500	2.5	4	7	16	3	
TP432	TPA432	4 Pin 32 A Round Pin Plug	32	500	2.5	16	9	28	3	
TP440	-	4 Pin 40 A Round Pin Plug	40	500	2.5	16	9	28	3	
TP450	-	4 Pin 50A Round Pin Plug	50	500	2.5	25	9	28	3	
TP510	TPA510	5 Pin 10 A Round Pin Plug	10	500	2.5	4	7	16	3	
TP520	TPA520	5 Pin 20 A Round Pin Plug	20	500	2.5	4	7	16	3	
TP532	TPA532	5 Pin 32 A Round Pin Plug	32	500	2.5	16	9	28	3	
TP540	-	5 Pin 40 A Round Pin Plug	40	500	2.5	16	9	28	3	
TP550	-	5 Pin 50 A Round Pin Plug	50	500	2.5	25	9	28	3	

Outline & Mounting Dimensions

